

Analogue CCTV / HD 4n1 / Cameras / Bullet Cameras

UV-UAC-B112-F40

Uniview



Features

- Uniview
- Analog Bullet Camera
- 1/3" Progressive Scan CMOS
- 2 Megapixel (1920x1080)
- 4 mm Lens
- 0.02 Lux
- IR Range 20 m
- Weatherproof IP67
- IR Cut
- TVI/AHD/CVI/CVBS

Specifications

Range	Uniview
Image sensor	1/3" Progressive Scan CMOS
Maximum resolution	2 Megapixel (1920x1080)
Main Stream rate	1080p (1920x1080)
Extra Stream rate	720p (1280x720)
Lens	4 mm
Viewing Angle (FOV)	100.9° (H), 56.5° (V),121.8° (D)
Minimum illumination	0.02 Lux (Colour)
Infrared range	20 m
Image improvements	BLC, HLC, DWDR, DAY/NIGHT MODE, 2D. DWDR. SMART IR
Day / Night	Mechanical ICR filter
Invert image (Flip)	Supports horizontal rotation of 180° and vertical rotation of 180°
Power	DC 12V / 2.88W
Video output	BNC, supports TVI, AHD, CVI and CVBS
Interface	5.5 mm
Temp. operation	-30° C ~ 60° C
Degree of protection	Weatherproof IP67
Dimensions	142mm (L) * 63mm (W) * 65mm (H)
Weight	145 g