

IP CCTV / Professional NVRs / Uniview - Uniarch

UV-NVR-110E2

Uniarch



Features

- Uniarch
- NVR for IP cameras
- 10 CH
- 64 Mbps bandwidth supported
- Maximum resolution 8 Megapixel
- Compression Ultra265/H.265/H.264
- VGA HDMI 4K and VGA output
- Mouse
- Space for 1 HDD
- WEB, CMS, Smartphone and NVR interface
- ONVIF Compatible

Specifications

Brand	Uniarch
Inputs for IP cameras	LAN port up to 10 channels
IP compatible cameras	UNIVIEW, ONVIF
Bidirectional audio	1 RCA output
Video outputs	1 HDMI 4K, 1 VGA
Video compression format	Ultra H.265 / H.265 / H.264
Display resolution	3840x2160, 1920x1080, 1600x1200, 1280x1024, 1280x720, 1024x768
Total bandwidth	64 Mbps downstream / 32 Mbps upstream
Main Stream recording	4K / 5Mpx 4Mpx 3Mpx / 1080p / 960p 720p / D12CIF / CIF
Decoding	1x4K @ 30fps / 1x5MPx @ 30fps / 2x4MPx @ 30fps / 2x3MPx / 30fps @ 4x1080p / 8x720p / 30fps @ 10xD1 / 30fps @ [%VAR%]
External Backup	USB / HDD USB memory
Internal memory	1 SATA HDD 3.5" of up to 6 TB (not included)
Communication	1 x USB 2.0 / 1 x USB 3.0 / 1 x RJ45 (Ethernet)
Remote access	Web browser, Smartphone App & PC Software
Power	DC 12 V
Dimensions / Weight	46(Al) x 260(An) x 246 (D) mm / 1 Kg